

PRODUCT SPECIFICATIONS:

TURBINE FUEL, LSR

<u>PROPERTY</u>	<u>ASTM TEST METHOD</u>	<u>SPECIFIED LIMIT</u>
Gravity, API @ 60°F	D287	60-75
Gravity, Specific 60/60°	---	0.6852 - 0.7389
Density, lb./gal @ 60°F	---	---
Cloud Point, °F	D5773	-10 Maximum
Distillation Temperature, °F	D86	
Initial Boiling Point	---	---
10% Recovered	---	Report
50% Recovered	---	Report
90% Recovered	---	Report
Final Boiling Point	---	---
Distillation Residue, vol. %	---	1.5
Distillation Loss, vol. %	---	1.5
Recovery, vol. %	---	Report
Olefins, vol. %	D1319	5.0 Maximum
Aromatics, vol. %	D1319	25 Maximum
Color, Saybolt	D156	Report
Copper Strip Corrosion	D130	1b Maximum
Existent Gum, mg/100 ml	D381	7 Maximum
Net Heat of Combustion, BTU/lb	D1405 ---	---
Sulfur, Total, wt. %	D2622	18,400 Minimum
Viscosity, cSt @ 104°F	D445	0.01 Maximum
Vanadium, ppm	D2787	1.0 Maximum
Sodium and Potassium, ppm	D2788	0.5 Maximum
Calcium, ppm	D2788	1.0 Maximum
Lead, ppm	D2787	1.0 Maximum

Revised: May 1, 1999

By: _____